


MARINER POST TOP LED LANTERN



DIMENSIONS



FIXTURE	A	B
MARI-PT	27.5"	20.75"

DESCRIPTION

An outstanding traditional design and authentic appearance that is suitable for a variety of lighting applications. The MARI-PT by AV Poles and Lighting is ideal for commercial, municipal, and design build lighting applications.

FEATURES

- Stainless steel hardware
- 0-10V dimmable driver
- 10-20KV surge protection
- IP67 rated modules - 5 year warranty
- Up to 180 Lumens Per Watt output
- Low maintenance cost with lifetime >54,000 hrs
- LED modules arranged in a Type V optic pattern for even light distribution.
- Lens available in acrylic or polycarbonate construction with clear patterned or smooth opal finish.
- TGIC thermoset polyester powder coat finish is electrostatically applied at a 3.0 mil nominal thickness. A five stage metal pre-treatment process and sealer provide maximum corrosion resistance. The powder top coat is baked in excess of 400 degrees for supreme endurance.



ORDERING INFORMATION

AVPL -

LUMINAIRE	WATTAGE	COLOR TEMP	VOLTAGE	LENS	MOUNTING	FINISH	OPTIONS
MARI-PT	40W 350mA	3000K WARM WHITE	120-277V VOLTAGE SENSING	CSA CLEAR SMOOTH ACRYLIC	PT23 Ø2.375" TENON	DARK BRONZE	LOUVERS INTERNAL
	58W 525mA	4000K NEUTRAL WHITE	347-480V VOLTAGE SENSING	CSP CLEAR SMOOTH POLYCARBONATE	PT27 Ø2.875" TENON	BLACK	HOUSE-SIDE SHIELD
	80W 700mA	5000K COOL WHITE		OSA* OPAL SMOOTH ACRYLIC	PT30 Ø3" TENON	WHITE	PHOTOCELL BUTTON
	116W 1050mA			OSP* OPAL SMOOTH POLYCARBONATE		GREY	3PIN* RECEPTACLE
						GREEN	7PIN* RECEPTACLE
				* APPLY 11% OF 10% TO LUMEN OUTPUT CHART	CONTACT FACTORY FOR OTHER SIZES	ALL RAL COLORS AVAILABLE	* REQUIRES TYPE D - UTILITY FITTER

LUMEN OUTPUT CHART

3K		40W 350mA	58W 525mA	80W 700mA	116W 1050mA	4K		40W 350mA	58W 525mA	80W 700mA	116W 1050mA	5K		40W 350mA	58W 525mA	80W 700mA	116W 1050mA
	Type V	5,472	7,470	9,664	13,084		Type V	5,760	7,841	10,176	13,827		Type V	5,817	7,919	10,277	13,965