



Job Name:		
Job Location:		


Type: Quote Date:

AV POLES & LIGHTING 43827 Division St. Lancaster, CA 93535 Toll Free: (844) 770-AVPL Fax: (661) 945-2764 sales@avpltg.com www.avpltg.com

ACORN LARGE SERIES



DIMENSIONS





FIXTURE	Α	В		
AL-CC	22.5"	16.5"		

DESCRIPTION

This traditional Acorn is an inexpensive solution for a variety of lighting applications. The AL-CC series by AV Poles and Lighting is ideal for commercial, municipal, and design build applications.

FEATURES

- · Cast aluminum crown, cage, and fitter
- Stainless steel hardware
- 0-10V dimmable driver

Client Name

Quote:

- 10-20KV surge protection
- IP67 rated modules 5 year warranty
- Up to 180 Lumens Per Watt output
- Low maintenance cost with lifetime >54,000 hrs
- LED modules arranged in a Type V optic pattern for even light distribution.
- Lens available in acrylic or polycarbonate construction with clear patterned or smooth opal finish.
- TGIC thermoset polyester powder coat finish is electrostatically applied at a 3.0 mil nominal thickness. A five stage metal pre-treatment process and sealer provide maximum corrosion resistance. The powder top coat is baked in excess of 400 degrees for supreme endurance.











ORDERING INFORMATION

AVPL - _____ - ____ - ____ - ____ - ____ - ____ - ____ - ____ - ____ - ____ - ___

LUMINAIRE	WATTAGE	COLOR TEMP	VOLTAGE	LENS	FITTER	MOUNTING	FINISH	OPTIONS
AL-CC	40W 350mA	3000K WARM WHITE	120-277V VOLTAGE SENSING	CPA CLEAR PATTERNED ACRYLIC	А ѕмоотн	PT23 Ø2.375" TENON	DARK BRONZE	PF FINIAL
	58W 525mA	4000K NEUTRAL WHITE	347-480V VOLTAGE SENSING	CPP CLEAR PATTERNED POLYCARBONATE		PT27 Ø2.875" TENON	BLACK	LOUVERS Internal
	80W 700mA	5000K COOL WHITE		OSA* OPAL SMOOTH ACYLIC		PT30 Ø3" TENON	WHITE	HOUSE-SIDE SHIELD
	116W 1050mA			OSP* OPAL SMOOTH POLYCARBONATE	B FLUTED		GREY	PHOTOCELL BUTTON
							GREEN	FSP211 MOTION SENSOR
								3PIN RECEPTACLE
					C			7PIN RECEPTACLE
				***************************************		CONTACT		
				*APPLY LLF OF 10% TO LUMEN OUTPUT CHART		CONTACT FACTORY FOR OTHER SIZES	ALL RAL COLORS AVAILABLE	

LUMEN OUTPUT CHART

$\overline{\mathbf{Y}}$		40W 350mA	58W 525mA	80W 700mA	116W 1050mA	¥		40W 350mA	58W 525mA	80W 700mA	116W 1050mA	¥		40W 350mA	58W 525mA	80W 700mA	116W 1050mA
က	Type V	5,472	7,470	9,664	13,084	7	Type V	5,760	<i>7</i> ,841	10,1 <i>7</i> 6	13,827	2	Type V	5,817	<i>7</i> ,919	10,277	13,965